

CE 15 Mobipack Portable Waste Compactor

Twin Ram Heavy Duty
Optional Liquid Retentive System

Reduction of waste disposal costs

*Reduction of labour costs
involved in waste handling*

Fewer vehicles entering premises.



No expensive concrete base required

Improvement in good housekeeping and hygiene

Improved security and reduced fire risks

No ongoing container rentals

DICOM
LIMITED

Lydford Road, Meadow Lane Industrial Estate,
Alfreton, Derbyshire DE55 7RQ

Tel: 01773 520565. Fax: 01773 520881 e-mail: sales@dicom.ltd.uk

DICOM LIMITED

Lydford Road, Meadow Lane Industrial Estate,
Alfreton, Derbyshire DE55 7RQ
Tel: 01773 520565. Fax: 01773 520881 e-mail: sales@dicom.ltd.uk

COMPACTORS

Static

Portable

Liquid Retentive

Front End Loaders

Pre-Crush

Balers

Multi Chamber Balers

Extruders

Drum Crushers

De-watering

Can Crushers

The CE 15 Mobipack Portable Waste Compactor

The CE15 twin ram portable incorporates the modern octagonal design and has the option of a liquid retentive door seal. This system offers maximum benefits for waste producers with restricted space or putrescible waste. It is ideal for Hotels, Universities, Hospitals, Restaurants, Food processors etc.

SPECIFICATION

Machine Capacity	CE15 12.12m ³ (15.85yd ³)
Compaction Force	26 tonnes
Cycle Time	32 seconds
Charge Box Volume	0.9m ³ (1.2yds)
Volume per Hour	101m ³ (132yds ³)
Hydraulic cylinders	2 x 101mm (4")
Motor	5.5kW (7.5hp) 20amp 3 phase 415 volt

ELECTRICAL

Also available in single phase
Programmable Logic Controller (PLC) 24 volt

STANDARD CONTROLS

Keylock, start, auto reverse, 3/4 full warning light, safety circuit warning lamp and emergency stop

MACHINE DIMENSIONS

Loading Height	1143mm (45")
Length (o/a)	4395mm (173")
Width (o/a)	1870 (73.5")
Height (o/a)	2200mm (86.5")
Door Opening	1105mm x 762mm (43.5" x 30")

SAFETY: All machines are issued with a certificate of conformity, CE marked and include dual safety switches and dual safety monitoring circuits. 24 volt controls and emergency stops are fitted as standard.

STANDARD FEATURES

- Programmable Logic Controller (PLC).
- 3/4 Full warning light.
- Automatic shut down when container is full.
- Unique octagonal shape body, no rust traps, easy to clean
- Bustle gate rear door, increases Compaction.
- Optional built in or remote power pack
- Low loading height
- Exclusive 115° ram sweep system.
- Stress engineered for long life.
- Optional liquid retentive system.
- Available in various sizes.
- 12 Months guarantee.
- Regular service and maintenance contracts, extended warranties, steam cleaning service available.
- Nationwide service organisation.



Certificate No: A5946



The Service Team

esa

Member of the Environmental Services Association



We reserve the right to make changes to the technical specification of the machinery without notice.