



# DICOM

## PAALGROUP

The UK's premier manufacturer of waste compactors and balers

**Compactors :**

Static  
Portable  
Liquid Retentive  
Pre Crush

**Balers :**

Vertical  
Multi Chamber  
Horizontal  
Manual &  
Automatic

Drum Crushers  
Extruders  
De-Waterers

### Mobipack Rolonof Portable Waste Compactor Twin Ram Heavy Duty Optional Liquid Retentive system

*Reduction of labour costs  
involved in waste handling*

*No ongoing  
container rentals*

*Reduction of waste  
disposal costs*

*Fewer Vehicles  
entering premises*



Rear Tipper



Enclosed Hopper



Open Splayed Hopper

*No expensive concrete base required*  
*Improvement in good housekeeping and hygiene*

*Improved security and reduced fire risks*



## Mobipack Rolonof Portable Waste Compactor

This latest twin ram portable incorporates the modern container design and has a liquid retentive door seal. This system offers maximum benefits for Industry, Restaurants, Hospitals, Hotels, Supermarkets, Shopping Centres, Food processors etc.

### SPECIFICATIONS

	<b>CE32/30</b>
Machine Capacity	25 m <sup>3</sup> (32 yd <sup>3</sup> )
Compaction Force	30 tonnes
Blade Penetration	305 mm (12")
Cycle Time	48 seconds
Charge Box Volume	1.3 m <sup>3</sup> (1.7 yd <sup>3</sup> )
Volume per Hour	97.5 m <sup>3</sup> (127.5 yd <sup>3</sup> )
Hydraulic Cylinders	2 x 114 mm (4.5")
Motor	5.5 kW, 20 amp, 3 phase, 415 volt

### ELECTRICAL

Programmable Logical Controller (PLC) 24 volt,

### STANDARD CONTROLS

Keylock, Start, Auto Reverse,  $\frac{3}{4}$  Full Warning Light, Safety Circuit Warning Lamp and Emergency Stop

### MACHINE DIMENSIONS

Loading Height	1330 mm (52")
Length (o/a)	6412 mm (252")
Width (o/a)	2495 mm (98")
Height (o/a)	2745 mm (108")
Top Opening	1700 mm x 1100 mm (67" x 43.5")
Ram Depth	700 mm (27.5")

**SAFETY** : All machines are issued with a certificate of conformity, CE marked and include dual safety switches and dual safety monitoring circuits. 24 volt controls and Emergency Stops are fitted as standard.

### STANDARD FEATURES

- Liquid Retentive
- Twin Rams
- Programmable Logical Controller (PLC)
- $\frac{3}{4}$  Full warning light
- Automatic shut down when container is full
- Easy to clean
- Bustle gate rear door, increases Compaction
- 12 Months guarantee
- Optional built in or remote power pack
- Low loading height
- Full size compaction blade
- 1700 x 700 mm (67" x 28")
- Stress engineered body
- Made to measure systems available including dock loading, open and enclosed hoppers, chutes and tippers etc.
- Retaining teeth on header bar
- Regular service and maintenance contracts, extended warranties
- Nationwide service organisation

For further information on Dicom's wide range of Compaction Equipment, please contact our Alfreton Office.



**Nationwide Service is provided by Dicom's Engineers**



**LYDFORD ROAD, MEADOW LANE INDUSTRIAL ESTATE,  
ALFRETON, DERBYSHIRE. DE55 7RQ**

**Telephone : 01773 520565 Fax : 01773 520881**

**www.dicom.ltd.uk e-mail : sales@dicom.ltd.uk**

We reserve the right to make changes to the technical specification of the machinery without notice.